

International Journal of Ethics in Engineering & Management Education Website: www.ijeee.in (ISSN: 2348-4748, Volume 3, Issue 6, June 2016)

Symbol Detection and power optimization in MIMO-OFDM System using PSO

G.Koteswar Rao Research Scholar, ECE Dept, JNTU Hyderabad, Telangana, India e-mail:koteshganna@gmail.com

ABSTRACT: This paper proposed new detection scheme to improve the performance of terminals mobile transmissions at high speeds, low cost and low power consumption. Indeed, the increase in rates implies that the transmission channels are more difficult, making the task of receivers more difficult, we are interested in solving the classical problem of detection of a linear mixture of Gaussian noise for MIMO OFDM telecommunication systems from a noisy observation of an input signal mixed with a known matrix representing the behavior of the channel, we seek the vector minimizing the Euclidean distance between the noisy output and the noiseless one. MIMO OFDM systems have large frequency diversity. In this context, we investigate in a first part in the study of performance of conventional equalizers (ML, ZF, MMSE...). In a second part, we propose a detection algorithm and power allocation process with near-optimal performance in terms of bit error rate BER very close to ML called PSO (Particular Swarm Optimization) for its complexity relatively small compared to other detectors.

Keywords: MIMO, OFDM ,ZF , MMSE, ML ,PSO, BER , SNR,PA.

I.INTRODUCTION

The area of wireless communication and mobile communication are significant challenges. Over time, several generations have passed to improve the speed and capacity while maintaining an appreciable quality of service. By using multiple antennas at both transmitter and receiver (MIMO system) the throughput can be increased by simultaneously transmitting different streams of data on the different transmit antennas but at the same carrier frequency. In addition, the orthogonal frequency-division multiplexing (OFDM) has a potential to increase spectral efficiency. The combination of the throughput enhancement of MIMO system with the robustness of orthogonal frequency division multiplexing (OFDM) against frequency-selective fading caused by severe multipath scattering and narrowband interference is regarded as a very promising basis for future high speed data communication.

Dr. G. Laxminarayana Principal, Anuraag College of Engineering, JNTU Hyderabad, Telangana,India e-mail: gln9855@gmail.com

In this paper proposed some solutions to improve the performance of terminals mobile transmissions at high speeds, low cost, and low power consumption. Indeed, the increase in rates implies

that the transmission channels are more difficult, making the task of receivers more difficult. we are interested in solving the classical problem of detection of a linear mixture of Gaussian noise for MIMO OFDM telecommunication systems from a noisy observation of an input signal mixed with a known matrix representing the behavior of the channel, the vector minimizing the Euclidean distance between the noisy output and the noiseless one. MIMO OFDM systems have large frequency diversity. In this first investigated performance of different context, conventional equalizers like ML, ZF, MMSE and later proposed a detection algorithm with near-optimal performance in terms of bit error rate BER very close to ML called PSO (Particular Swarm Optimization) for its complexity relatively small compared to other detectors.

However, for these systems symbol detection is required at the receiver for coherent demodulation, but MIMO detection is computation extensive and not a trivial work. Various algorithms such as maximum likelihood (ML), zero forcing (ZF) and minimum mean square error (MMSE) algorithms have been proposed to detect symbols. Although the implementation of ZF and MMSE are quite easy and also less complex algorithm, it underperforms in fast fading and time varying environments. In comparison with other algorithm, ML algorithm reveals excellent performance in these environments. But the main drawback of ML is its extremely high computational complexity. It searches the candidate symbol vector on each subcarrier and Euclidean distance between received and actual symbol is computed in all the possible combinations of transmitted symbols. In addition to this, search space grows exponentially with the number of transmitter and receiver antennas, so computational complexity becomes intensive.



Website: www.ijeee.in (ISSN: 2348-4748, Volume 3, Issue 6, June 2016)

In this research work, different detection algorithms are analyzed their performances and in order to reduce the search space of ML detector and to reduce the computational complexity, proposed a heuristic approach PSO.

II.PROBLEM FORMULATION

Before introducing the signal detection, briefly describe a MIMO-OFDM system. Figure 1 shows the simplified block diagram of MIMO-OFDM system. For this system, we consider N_{tx} transmit, N_{rx} receive antennas, *n* OFDM symbols and *K* subcarriers. Data stream is mapped on to complex symbols considering modulation type. The transmitted symbol vector is expressed as



Fig.1.Block diagram of MIMO-OFDM system

$$S[n,k] = [S_1(n,k), \dots, S_{Ntx}(n,k)]^T, k = 0....1$$
(1)

Where $S_i[n, k]$ is symbol which is transmitted at the n_{th} symbol, k_{th} subcarrier and i_{th} antenna. [.]^T is transpose operation. By applying inverse fast Fourier transform (IFFT), symbol vectors are turned into OFDM symbol:

$$S_n[m] = \frac{1}{\sqrt{kN_{tx}}} \sum_{k=0}^{k=1} S\{n, K\} e^{\frac{j2\pi m}{k}}, \ m = 0, 1, \dots, k$$
(2)

To eliminate inter symbol interference (ISI) added cyclic prefix (CP), and then signal vectors are fed though the i_{th} transmitter antenna. In reception CP is removed from signal vector at q_{th} receiver antenna and fast Fourier transform (FFT) is applied.

Then the received signal vector can be expressed as

$$Y_{q}[n,k] = \sum_{k=0}^{k=1} H_{i}[n,k] S_{i}[n,k] + W_{q}[n,k]$$
(3)

 $H_i[n, k]$ is channel impulse response vector and $W_q[n, k]$ is additive white Gaussian noise. The task is detecting N_{tx} transmitted symbols S from a set of N_{rx} observed symbols Y that have passed through a non-ideal communication channel H, typically modelled as a linear system followed by an AWGN.



ZF, MMSE and ML equalizers performances: In MIMO systems let the channel is multi – fading to compare the characteristic BER according to the SNR for MMSE, ZF and ML Equalizer, for simulation used QAM-4 modulation for 2 × 2 MIMO-OFDM system with 64 subcarriers and length of the Cyclic prefix is 16. The result of this comparison is shown in the Figure 2.



Fig.2 BER according to SNR for ZF, MMSE and ML detector

In Figure 2, the bit error rate (BER) versus the signal-to-noise ratio (SNR) performance of symbol detectors in the 2 × 2 MIMO- OFDM systems is shown. As it can be seen, the ML has better performance than ZF and MMSE algorithms. For optimal solution of ML detection, all $M N_{tr}$



Website: www.ijeee.in (ISSN: 2348-4748, Volume 3, Issue 6, June 2016)

possible combination of transmitted symbols must be searched. For this reason, the computational complexity increases with transmitter antenna.

III.SYMBOL DETECTION

Transmitted symbols from a known finite alphabet $v = \{x_1, ..., x_M\}$ of size M are passed to the channel. The detector chooses one of the M^{Ntx} possible transmitted symbol vectors from the available data. Assuming that the symbol vectors $x \in V_{Ntx}$ are equiprobable, the maximum likelihood (ML) detector always returns an optimal solution according to the following:

$$X = \arg_{x \in V_{Ntx}} \max P(y \text{ is observed was sent})$$
(4)

Assuming the additive noise w to be white and Gaussian, the ML detection problem can be expressed as the minimization of the squared Euclidean distance to a target vector y over N_{tx} -dimensional finite discrete search set

$$X = \arg_{x \in V_{Ntx}} \min \| y - Hx \|^2$$
(5)

The optimal ML detection scheme needs to examine all M_{Ntx} or 2^{bNtx} symbol combinations (b is the number of bits per symbol). The problem can be solved by enumerating over all possible x and finding the one that causes the minimum value as in above equation. Therefore, the computational complexity increases exponentially with constellation size M and the number of transmitters N_{tx} , present PSO algorithms-assisted MIMO-OFDM symbol detectors thus viewing the MIMO symbol detection issue as a combinatorial optimization and approximate the near optimal solution iteratively with lesser than ML computational complexity.

A swarm consists of No. of particles (possible solutions) that move (fly) through the feasible solution space to explore the optimal solution that can be coded as binary strings or real valued vectors. The particles are capable of interacting with each other in a given neighborhood and traverse a search space where a quality measure, fitness, can be evaluated. The particles are evolved through cooperation and competition among themselves over iterations. The coordinates of each particle represent a possible solution associated with two vectors, position (X_i) and velocity (V_i) . Each particle experiences an iterative procedure of adaptation to two types of major information, i.e. individual learning and cultural transmission, which means that the procedure accelerates particles at each time step towards personal best (best value recorded by each particle) and the position of the

most recent global best point (best position returned from the swarm).

A key attractive feature of the PSO approach is its simple mathematical model involving two model equations and fewer parameters to adjust [66].

IV.DETECTION ALGORITHM

An important step to implement PSO is to define a fitness function; this is the link between the optimization algorithm and the real-world problem. The fitness function is unique for each optimization problem. The fitness function using the coordinates of the particle returns a fitness value to be assigned to the current location. If the value is greater than the value at respective personal best (pbest) for each particle or global best (gbest) for the swarm, then previous locations are updated with the present locations.

The velocity of the particle is changed according to the relative locations of pbest and gbest. Once the velocity of the particle is determined, it simply moves to the next position. After this process is applied on each particle, it is repeated till the maximum number of iterations are reached.



Fig.3. Flow chart depicting the PSO Algorithm

The proposed MIMO detection algorithm based on standard continuous PSO [67] is described below:

1. Initialize the particle size (swarm) by taking the initial solution guess. Initialize the algorithm parameters.

2. Fitness of each particle is calculated using (5):



Website: www.ijeee.in (ISSN: 2348-4748, Volume 3, Issue 6, June 2016)

(6) $f = ||v - Hx||^2$ Minimum Euclidean distance for each symbol represents the fitness of solution. Find the global best performance 'gbestid' in the population that represents the least Euclidean distance found so far. Record the personal best 'pbestid' for each bit along its previous values.

3. Velocity for each particle is computed using the following PSO velocity update equation:

 $V_{id}(k) = V_{id}(k-1) + \phi_1 \text{ rand } [\text{pbest}_{id} - x_{id}(k-1)] +$ ϕ_2 rand₂[gbest_{id}-x_{id}(k-1)] (7)4. The particle position is updated depending on the following

PSO velocity update equation:

$$x_{id}(k) = x_{id}(k-1) + v_{id}(k)$$
(8)

5. Repeat from step 2 until maximum number of iterations are reached. Here 'k' is the number of iterations. An optimum number of iterations are tuned for efficient performance. The solution gets refined iteratively.

V.POWER ALLOCATION

The received signal can be modeled under flat fading MIMOchannel as

$$\begin{bmatrix} y_1 \\ y_2 \\ \vdots \\ \vdots \\ y_r \end{bmatrix} = \begin{bmatrix} h_{11} & h_{12} & \dots & h_{1t} \\ h_{21} & h_{22} & \dots & h_{2t} \\ \vdots & \ddots & \vdots \\ h_{r1} & h_{r2} & \dots & h_{rt} \end{bmatrix} * \begin{bmatrix} x_1 \\ x_2 \\ \vdots \\ \vdots \\ x_t \end{bmatrix} + \begin{bmatrix} n_1 \\ n_2 \\ \vdots \\ \vdots \\ n_r \end{bmatrix}$$
$$y = Hx + n$$

Constant Instantaneous Total Rate (CITR)

Using CITR we can minimizes transmit power while keeping constant rate.

Now problem is defined as

minimize
$$\sum_{i=1}^{n} P_i$$

s.t. $C = \sum_{i=1}^{n} \log_2(1 + \frac{P_i \sigma_i^2}{\sigma^2})$

To obtain the solution for optimization problem, we again use Lagrangian theorem

$$L = \sum_{i=1}^{n} P_i + \lambda (C - \sum_{i=1}^{n} \log_2(1 + \frac{P_i \sigma_i^2}{\sigma^2}))$$

Now differentiate equation with respect to Pi and put equal to zero,

$$\begin{split} 1 + \lambda (-\frac{\frac{\sigma_i^2}{\sigma^2}}{1 + \frac{P_i \sigma_i^2}{\sigma^2}}) log_2 e &= 0\\ 1 + \frac{P_i \sigma_i^2}{\sigma^2} &= (\lambda \log_2 e) \sigma_i^2 / \sigma^2 \end{split}$$

Channel capacity can be rewritten as

$$C = \sum_{i=1}^{n} \log_2(1 + \frac{P_i \sigma_i^2}{\sigma^2}) = \log_2(\prod_{i=1}^{n} (1 + \frac{P_i \sigma_i^2}{\sigma^2}))$$

$$C = \log_2(\prod_{i=1}^{n} (\mu \sigma_i^2 / \sigma^2))$$
Where
$$\mu = \lambda \log_2 e$$

$$\mu = \frac{2^{C/n}}{(\prod_{i=1}^{n} \sigma_i^2 / \sigma^2)^{\frac{1}{n}}}$$

$$P_i = \mu - \frac{\sigma^2}{\sigma_i^2}$$
As power has to be positive

VI.SIMULATION RESULTS

The performance of PSO detector compared with ZF, MMSE and ML using 64 subcarriers, CP length is 16, BPSK for modulation and 2×2 MIMO-OFDM systems.

Fig5.5 shows the BER versus Eb/No performance of ZF, MMSE, ML and PSO detectors compared with ML for 2×2 MIMO-OFDM system. As it can be seen, PSO has better performance than ZF and MMSE algorithms and the BER performance PSO is close to the ML detectors. For instance, the BER difference between PSO and ZF is more than 10 at a 17-dB SNR value. However, a substantial ML complexity reduction is achieved using this proposed system. Here examined the computational complexity of the reported PSO-MIMO detector and formulate a theoretical expression for computational complexity.

A comparison with the conventional ML optimal detection method is also drawn. As the hardware cost of each algorithm is specific implementation, we try to provide a rough estimate of complexity in terms of the number of complex multiplications.

The computational complexity is computed in terms of the Ntx, Nrx and the constellation size M. For the ML detector as seen from (5) MN_{tx} ($N_{rx}N_{tx}$) multiplications are required for matrix multiplication operation and additional



Website: www.ijeee.in (ISSN: 2348-4748, Volume 3, Issue 6, June 2016)



Fig.4 BER according to SNR for ZF, MMSE, ML and PSO detector

| Power Allocation (PA) | 5dB (SNR) | 10dB (SNR) | 15dB (SNR) | 20dB (SNR) | 25dB (SNR) |
|--------------------------|--------------|---------------|---------------|---------------|---------------|
| EPA (BER) | 10-0.3 | 10-0.9 | 10-0.7 | 10-2.5 | 10-3.2 |
| PSO PA (BER) | 10-0.8 | 10-1.1 | 10-2.0 | 10-2.9 | 10-3.9 |

 $M N_{tx} N_{rx}$ multiplications are needed for square operation [8]. Therefore, *ML* complexity becomes

$$\xi_{ML} = N_{rx} \left(N_{tx} + 1 \right) M_{Ntx} \tag{9}$$

For the proposed detector, first fitness of each particle in population N_p using (5) is calculated. Multiplication complexity (ξ_{PSO}) becomes

$$\xi_{PSO} = N_p \left(N_{tx} N_{rx} \right) \tag{10}$$

Velocity update in *PSO* and pheromone updates require μ_{vel} additional multiplications per iteration from (7). To reduce some complexity w = 1 and $\phi_1 = \phi_2 = 1$ is assumed. Therefore, the complexity becomes

$$\xi_{PSO} = N_p \left(N_{tx} N_{rx} + \mu_{vel} \right)$$

This procedure is repeated N_{itr} times to converge to the near optimal BER performance. Therefore,

$$\xi_{PSO} = N_p \left(N_{tx} N_{rx} + \mu_{vel} \right) N_{itr}$$
(12)

The complexity of ML is exponential with N_{tx} and M.

This increase is even significant with higher-order modulation schemes in MIMO systems with more transmitters. However, this complexity estimate is only meaningful in the order-ofmagnitude sense since it is based on the number of complex multiplications only. The above complexity is estimated on subcarrier-by-subcarrier for the MIMO-OFDM system [7].

VII.CONCLUSION

The synthesis of new systems aims to transmission of digital information at higher bandwidths and service for a quantity more demanding. After the presentation of the basic principles of digital transmission and exposure characteristics of the linear model of the wireless channel, examples of systems studied in the literature and depicted as linear radio channels are given and an analysis of detection techniques under optimal suboptimal most popular is described. These sensors have no compromise between performance and complexity; note for example that the simple linear detectors have poor performance as maximum likelihood detectors which have a computational complexity much more complex. The different detection algorithms such as ZF, MMSE and ML results shows that ML is the optimal detector, but with a search space and the high computational complexity. So, proposed PSO approach particle detection shows promising results. Their swarm PSO simple mathematical model, reducing the complexity of implementation, resistance to being trapped in local minima, convergence guaranteed with a reasonable solution to make fewer iterations these techniques inspired by nature a suitable candidate for the detection symbol in real time in the MIMO-OFDM system. The PSO algorithm has its own means of ingenious natural to explore the search space to find an optimal solution from a surface complexity of ML detector expensive. The effectiveness of algorithm is also a simple calculation code in the central algorithm with few parameters to adjust. Reducing the computation time with higher order modulations and antenna transmission make these detection algorithms proposed system particularly useful for high rate data transmission.

REFERENCES

- Dr. Anubhuti Khare, Manish Saxena, Vijendra singh mandloi. (2012). Performance Analysis of V-Blast Based MIMO-OFDM System with Various Detection Techniques, IOSR Journal of Engineering (IOSRJEN), 2 (1) 166-169, January.
- [2]. Kiessling, M., Speidel, J. (2003). Analytical performance of MIMO zero-forcing receivers in correlated rayleigh fading environments, In: Proceedings of the 4th IEEE Workshop on Signal Processing Advances in Wireless Communication, Rome, Italy, p. 383-387.
- [3]. Jiang, M., Akthman, J., Guo, F., Hanzo, L. (2006). Iterative joint channel and symbol detection for multiuser MIMO-OFDM, In:

(11)



Website: www.ijeee.in (ISSN: 2348-4748, Volume 3, Issue 6, June 2016)

Proceedings of the IEEE 63th Vehicular Technology Conference, Melbourne Australia, p. 221-225.

- [4]. Liang, Y. M., Luo, H. W., Huang, J. G. (2006). RLS channel estimation with adaptive forgetting factor in space time coded MIMO-OFDM systems, Journal of Zhejiang University Science, 7, 507-515.
- [5]. Kennedy, J., Eberhart, RC. (2001). Swarm Intelligence. Morgan Kaufman Publisher: Los Altos, CA.
- [6]. Khan, A. A., Bashir, S., Naeem, M., Shah, S. I. (2006). Optimized detection in multi-antenna system using particle swarm algorithm. Third International Conference on Intelligent Systems, Prague, Czech Republic, August, p. 25–27.
- [7]. Adnan Ahmed Khan. (2008). Symbol detection in spatial multiplexing system using particle swarm optimization metaheuristics, International Journal of Communication Systems, Int. J. Commun. Syst.Published online in Wiley Inter Science.
- [8]. Khan, A. A., Naeem, M., Shah, S. I. (2007). A particle swarm algorithm for symbols detection in wideband spatial multiplexing systems, In: Proceedings of the 9th Annual Conference on Genetic and Evolutionary Computation, London England, p. 63-69.
- [9]. Marzetta, Thomas L. "Noncooperative cellular wireless with unlimited numbers of base station antennas." IEEE Transactions on Wireless Communications 9, no. 11 (2010): 3590-3600.